

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):



- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



1/4



Sensor Parameters

- TIME > TIME [seconds]
- 8237 > CH. 1 MAIN RAM POSITION [inches]
- 8238 > CH. 2 MAIN RAM POSITION [inches]
- 8239 > CH. 1 MCV POSITION [inches]
- 8240 > CH. 2 MCV POSITION [inches]
- 8241 > CH. 1 SERVOAMP CURRENT [milliamps]
- 8242 > CH. 2 SERVOAMP CURRENT [milliamps]
- 8243 > CH. 3 SERVOAMP CURRENT [milliamps]
- 8244 > CH. 4 SERVOAMP CURRENT [milliamps]
- 8245 > CH. 2 FAIL SENSOR NO. 1 LVDT POSITION [Vrms]
- 8246 > CH. 2 FAIL SENSOR NO. 2 LVDT POSITION [Vrms]
- 8201 > STABILATOR ACTUATOR COMMAND [INCHES]
- 8268 > LOAD ACTUATOR COMMAND [pounds]
- 8312 > LOAD ACTUATOR LOAD CELL FORCE [LBS]
- 8430 > HYDRAULIC SYSTEM 1 FLUID TEMPERATURE [deg F]
- 8431 > HYDRAULIC SYSTEM 2 FLUID TEMPERATURE [deg F]
- 8432 > LOAD CYLINDER HYDRAULIC SUPPLY TEMPERATURE [deg F]
- 8433 > LOAD CYLINDER HYDRAULIC RETURN TEMPERATURE [deg F]
- 8015 > STABILATOR ACTUATOR SYSTEM 1 INLET PRESSURE [psi]
- 8016 > STABILATOR ACTUATOR SYSTEM 1 OUTLET PRESSURE [psi]
- 8013 > STABILATOR ACTUATOR SYSTEM 2 INLET PRESSURE [psi]
- 8014 > STABILATOR ACTUATOR SYSTEM 2 OUTLET PRESSURE [psi]

210

FIG. 3




FIG. 4

4/4

500




FIG. 5